


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 900/60 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	187 D



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94075096	<b>RC (IN)</b>	238.3
<b>SW (IN)</b>	34.7	<b>RIM REC</b>	DW 30 B
<b>OD (IN)</b>	80.5	<b>ECE</b>	E11-106R-009004
<b>SLR (IN)</b>	34.7	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	9580	11140	12910	14470	16040	17600	19550
<b>FROM 40 TO 25</b>	10530	12250	14190	15910	17620	19340	21490
20	10740	12490	14460	16210	17970	19730	21920
12	10950	12730	14750	16530	18320	20120	22350
5	11570	13470	15600	17490	19380	21270	23640
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	14740	17140	19850	22270	24670	27080	30090
5 HT	10740	12490	14460	16210	17970	19730	21920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.