


AGRIMAX V- FLECTO



TIRE SIZE	VF 650/85 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR DE ALTA POTENCIA / TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	182 D

DIMENSÕES IS STANDARD

SW (MM)	670	RIM REC	DW 23 B
OD (MM)	2071	RIM ALT	DW 20 B; DW 21 B
SLR (MM)	887	ECE	E11-106R-0010945
RC (MM)	6119	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2
70	3865	4485	5105	5800	6420	7035	7735
FROM 65 TO 40	4250	4930	5610	6375	7055	7735	8500
30	4335	5025	5720	6500	7195	7885	8670
20	4420	5125	5830	6630	7335	8040	8840
10	4675	5420	6170	7010	7760	8505	9350
*UPTO 10 CYC WITH FRONT LOADER	5950	6900	7850	8925	9875	10825	11900
10HT	4335	5025	5720	6500	7195	7885	8670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.