

# AS 504

<b>TIRE SIZE</b>	<b>4.00 - 16</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	TELESKOPLASTARE / ÅKERSLÄP / ARBETSFORDON / TELESKOPLASTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	66 A8
<b>LI/SS FREE ROLLING</b>	78 A8



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	110	<b>RIM REC</b>	3.00 D
<b>OD (MM)</b>	628	<b>RIM ALT</b>	2.50 C
<b>SLR (MM)</b>	296	<b>ECE</b>	E11-106R-005193
<b>RC (MM)</b>	1935	<b>PR</b>	4

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>2.80</b>
10 FR	595
25 FR	505
30 FR	475
40 FR	425
10 DW	420
25 DW	355
30 DW	335
40 DW	300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.