


# RIDEMAX IT 697 (M+S)

<b>TIRE SIZE</b>	<b>540/70 R 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	170 D ; 175 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	535	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	1370	<b>RIM ALT</b>	DW18 L
<b>SLR (MM)</b>	625	<b>ECE</b>	E11-106R-007933
<b>RC (MM)</b>	4181	<b>SRI</b>	650

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
65	2040	2520	2760	3240	3660	4080	4500	4920	5460	6000
50	2205	2725	2985	3500	3955	4410	4860	5315	5900	6480
40	2350	2900	3175	3730	4210	4695	5175	5660	6280	6900
30	2450	3025	3315	3890	4395	4900	5400	5905	6555	7200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.