

AGRIMAX RT 855

TIRE SIZE	380/85 R 24
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	131 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94044672	RC (IN)	146.5
SW (IN)	15.0	RIM REC	W 12
OD (IN)	49.4	RIM ALT	W 11; W 13
SLR (IN)	21.8	ECE	E4-106R-000592

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	2370	2760	3140	3530	3910	4300
25	2370	2760	3140	3530	3910	4300
20	2540	2950	3370	3780	4200	4610
5 LT	3170	3690	4210	4730	5250	5760
5 HT	2540	2950	3370	3780	4200	4610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.