

# TR 459

|                     |             |
|---------------------|-------------|
| <b>TYRE SIZE</b>    | 17.5L - 24  |
| <b>UM</b>           | IS STANDARD |
| <b>CONSTRUCTION</b> | ⊠ BIAS      |
| <b>MACHINERY</b>    | TRACTOR     |
| <b>VERSION</b>      | INDUSTRIAL  |
| <b>TYRE TYPE</b>    | TL          |
| <b>LI/SS</b>        | 148 A8      |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 445  | <b>RIM REC</b> | DW 15 L         |
| <b>OD (MM)</b>  | 1270 | <b>RIM ALT</b> | DW 14 L         |
| <b>SLR (MM)</b> | 557  | <b>ECE</b>     | E11-106R-004659 |
| <b>RC (MM)</b>  | 3825 | <b>PR</b>      | 12              |

## LOAD CAPACITY (KG/TYRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.70</b> |
| 40                | 3150        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.