

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>250/85 R 22</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / VINDIMADORA / TRATOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	113 A8/B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94049332	<b>RC (IN)</b>	116.7
<b>SW (IN)</b>	9.9	<b>RIM REC</b>	W 8
<b>OD (IN)</b>	38.8	<b>RIM ALT</b>	W 7
<b>SLR (IN)</b>	17.8	<b>ECE</b>	E11-106R-002973

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
<b>30</b>	1200	1380	1580	1770	1980	2180	2360	2540
<b>25</b>	1200	1380	1580	1770	1980	2180	2360	2540
<b>20</b>	1290	1480	1700	1910	2130	2350	2540	2720
<b>5 LT</b>	1610	1840	2120	2390	2670	2930	3170	3410
<b>5 HT</b>	1290	1480	1700	1910	2130	2350	2540	2720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.