

FLOTATION 558

TIRE SIZE	400/55 - 22.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ENFARDADEIRA DE FENO / CEIFEIRA / CISTERNA MÓVEL / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	140 A8/136 B
LI/SS FREE ROLLING	152 A8/148 B



DIMENSÕES US STANDARD

CÓDIGO USA	94006250	RC (IN)	121.4
SW (IN)	15.9	RIM REC	AG 11.75
OD (IN)	40.2	RIM ALT	12.25; 13.00; AG 13.00
SLR (IN)	17.5	ECE	E4-106R-002262

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	54	55	58
5 FR	10460	10640	10960
10 FR	9410	9570	9870
20 FR	8370	8510	8760
25 FR	7470	7590	7830
30 FR	6720	6830	6940
5 DW	7370	7480	7720
10 DW	6640	6730	6940
20 DW	5900	5990	6170
25 DW	5270	5350	5510
30 DW	4740	4820	4940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.