


AGRIMAX PROHARVEST

TIRE SIZE	VF 1000/55 R 32
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	197 D



DIMENSIONER US STANDARD

USA CODE	94076512	RC (IN)	224.5
SW (IN)	39.6	RIM REC	36.00 VA (multi-piece)
OD (IN)	74.8	ECE	E11-106R-0010574
SLR (IN)	33.1		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
45	10050	11610	13150	14960	16500	18300	20370	21910	23970	25770
FROM 40 TO 25	11060	12750	14450	16430	18130	20120	22390	24080	26350	28330
20	11280	13010	14750	16770	18510	20520	22840	24570	26880	28900
12	11500	13260	15030	17100	18860	20920	23280	25050	27400	29460
5	12160	14030	15890	18080	19950	22130	24620	26490	28990	31160
*UPTO 20 CYC	12540	14470	16400	18650	20580	22840	25410	27340	29900	32150
*UPTO 10 CYC	14980	17280	19590	22280	24580	27260	30330	32640	35710	38390
*UPTO 5 CYC	16410	18940	21460	24400	26930	29880	33240	35770	39130	42070
10HT	11280	13010	14750	16770	18510	20520	22840	24570	26880	28900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.