

AS 505



AS 505



AS 505 is best suited for soil tillage operations with trailers and implement machinery. It features excellent self-cleaning properties and increased traction on the ground, especially on muddy soil. The tire also ensures a long tire life-cycle.



SIZE	LI/SS		RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION	
			REC RIM	ALT RIM							
	DW	FR									
Ø15"	6.5/80 -15	86 A8	98 A8	5.0	4½ K 5 K 5 J	6.7	27.4	12.8	82.9	-	STD
	6.5/80 -15	92 A8	104 A8	5.0	4½ K 5 K 5 J	6.7	27.4	12.8	82.9	-	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
			
-	-	Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index	

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026