

EARTHMAX SR 46



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 46

EARTHMAX SR 46 for rigid haul trucks is BKT's innovative response to severe rocky, abrasive and harsh mining environments. This tyre has been specifically designed to carry heavy loads offering superior resistance to cuts and chips as well as a long tyre life-cycle. The All Steel casing and belts provide extraordinary protection against shocks, fatigue and flats to maximize uptime and enhance productivity.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø49"	27.00 R 49	TL	E4	**	223 B	19.50/4.0	-	590	746	2688	1225	8165	68	STD
	27.00 R 49	TL	E4	**	223 B	19.50/4.0	-	455	746	2688	1225	8165	68	CR
	27.00 R 49	TL	E4	**	223 B	19.50/4.0	-	655	746	2688	1225	8165	68	HRC
Ø51"	33.00 R 51	TL	E4	***	238 B	24.00/5.0	-	612	905	3050	1401	9377	87	CR

CR: CUT RESISTANT COMPOUND, STD: STANDARD, HRC: HEAT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES				
							
							

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 20/09/2026

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
					REC RIM	ALT RIM							
													
30.00 R 51	TL	E4	**	230 B	22.00/4.5	-	725	835	2895	1300	8800	77	HRC
33.00 R 51	TL	E4	**	235 B	24.00/5.0	-	800	905	3050	1401	9377	87	HRC
30.00 R 51	TL	E4	**	230 B	22.00/4.5	-	500	835	2895	1300	8800	77	CR
30.00 R 51	TL	E4	**	230 B	22.00/4.5	-	610	835	2895	1300	8800	77	STD
33.00 R 51	TL	E4	**	235 B	24.00/5.0	-	697	905	3050	1401	9377	87	STD
33.00 R 51	TL	E4	**	235 B	24.00/5.0	-	558	905	3050	1401	9377	87	CR

CR: CUT RESISTANT COMPOUND, STD: STANDARD, HRC: HEAT RESISTANT COMPOUND



TECHNOLOGIES			PERFORMANCES				
							
							

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 20/09/2026