


# FL 630 SUPER

650/55 R 26.5

UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	YAYICI / TANKER / RÖMORK / UYGULAMALI MAKINE
VERSION	STANDARD
TIRE TYPE	TL
	169 D



## UNDEFINED IS STANDARD

SW (MM)	645	RIM REC	AG 20.00
OD (MM)	1389	ECE	E4-106R-000806
SLR (MM)	627	SRI	650
RC (MM)	4258		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1690	1955	2220	2695	3120	3595	4070	4385	4860	5280
65	1860	2150	2440	2960	3425	3945	4470	4815	5340	5800
50	2250	2600	2950	3585	4145	4775	5410	5830	6460	7020
40	2525	2920	3315	4025	4660	5370	6080	6550	7260	7890
25	2935	3395	3850	4675	5410	6235	7060	7610	8435	9165
10	3345	3865	4385	5385	6160	7100	8040	8670	9605	10440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.