

AGRIMAX RT 955

TIRE SIZE	230/95 R 48
UM	IS STANDARD
MACHINERY	PULVÉRISATEUR / MACHINE À VENDANGER / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	136 D ; 139 A8



DIMENSIONS IS STANDARD

SW (MM)	228	RIM REC	W 7
OD (MM)	1656	RIM ALT	W 8
SLR (MM)	792	ECE	E11-106R-004067
RC (MM)	5085	SRI	800

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
65	785	920	1190	1435	1595	1680	1840	1995	2130	2240
50	825	970	1250	1510	1675	1770	1935	2100	2240	2355
40	855	1000	1290	1560	1730	1825	1995	2165	2310	2430
30	905	1060	1370	1655	1835	1935	2120	2300	2455	2580
10	1180	1380	1785	2155	2390	2520	2760	2995	3195	3360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.