


RIDEMAX FL 693 M



| | |
|---------------------|--|
| TIRE SIZE | 400/45 R 17.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | AUTOBOTTE / RIMORCHIO / ATTREZZI AGRICOLI |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 139 D |

DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CODICE USA | 94066063 | RC (IN) | 92.8 |
| SW (IN) | 15.7 | RIM REC | 14.00 |
| OD (IN) | 31.5 | ECE | E11-106R-006619 |
| SLR (IN) | 13.5 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 73 | 87 |
|-----------|------|------|------|------|------|------|------|------|------|------|------|
| 45 | 1220 | 1570 | 1960 | 2200 | 2550 | 2890 | 3170 | 3470 | 3810 | 4300 | 4880 |
| 40 | 1340 | 1720 | 2150 | 2410 | 2790 | 3160 | 3480 | 3810 | 4190 | 4720 | 5360 |
| 30 | 1630 | 2080 | 2600 | 2930 | 3380 | 3840 | 4220 | 4620 | 5070 | 5720 | 6490 |
| 25 | 1830 | 2340 | 2920 | 3280 | 3790 | 4300 | 4740 | 5180 | 5690 | 6420 | 7290 |
| 20 | 2030 | 2590 | 3240 | 3650 | 4210 | 4780 | 5270 | 5750 | 6320 | 7120 | 8090 |
| 15 | 2120 | 2710 | 3390 | 3810 | 4410 | 5000 | 5510 | 6020 | 6610 | 7450 | 8470 |
| 5 | 2410 | 3090 | 3860 | 4340 | 5020 | 5700 | 6270 | 6860 | 7530 | 8490 | 9640 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.