


AGRIMAX RT 657

TIRE SIZE	900/55 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	179 D ; 181 A8



DIMENSIONER IS STANDARD

SW (MM)	880	RIM REC	DW 27 B
OD (MM)	1950	RIM ALT	DW 30 B
SLR (MM)	880	ECE	E11-106R-006946
RC (MM)	5842	SRI	925

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8
65	3255	3800	4265	4805	5350	5890	6590	7055	7750
50	3420	3990	4480	5050	5620	6190	6920	7410	8140
40	3465	4045	4540	5115	5695	6270	7015	7510	8250
30	3745	4370	4905	5530	6155	6780	7580	8115	8915
10 LT	4365	5090	5715	6440	7170	7895	8830	9455	10385
10 HT	3745	4370	4905	5530	6155	6780	7580	8115	8915

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.