


# AGRIMAX RT 955

	<b>210/95 R 44</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	UYGULAMALI MAKINE / ÜZÜM HASAT MAKINESİ / BIÇERDÖVER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	120 A8/B



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	214	<b>RIM REC</b>	W 7
<b>OD (MM)</b>	1518	<b>RIM ALT</b>	W 6
<b>SLR (MM)</b>	721	<b>ECE</b>	E4-106R-000771
<b>RC (MM)</b>	4653	<b>SRI</b>	725

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8
50	660	760	870	980	1095	1205	1305	1400	-
40	660	760	870	980	1095	1205	1305	1400	-
30	705	810	930	1050	1170	1290	1395	1500	-
10	970	1115	1240	1365	1515	1660	1935	2040	2100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.