

# LG RIB

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>16X6.50 - 8</b>                           |
| <b>UM</b>           | US STANDARD                                  |
| <b>CONSTRUCTION</b> | ❖ BIAS                                       |
| <b>MACHINERY</b>    | ГАЗОНОКОСИЛКА / МИНИ-ТРАКТОР / ТРАКТОР-ТЯГАЧ |
| <b>VERSION</b>      | STANDARD                                     |
| <b>TIRE TYPE</b>    | TL   |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                              |
|-----------------|----------|----------------|------------------------------|
| <b>USA CODE</b> | 94030866 | <b>RC (IN)</b> | 46.6                         |
| <b>SW (IN)</b>  | 6.7      | <b>RIM REC</b> | 5.375   - 55;   - 70;   - 90 |
| <b>OD (IN)</b>  | 16.1     | <b>ECE</b>     | E11-106R-003372              |
| <b>SLR (IN)</b> | 7.2      | <b>PR</b>      | 10                           |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>72</b> |
| 10               | 1060      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.