

# AGRIMAX RT 765

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 420/70 R 24                                                                              |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | PULVERIZADOR / TRACTOR /<br>VENDIMIADORA / COSECHADORA /<br>MAQUINARIA AGRÍCOLA          |
| VERSIÓN      | SPECIAL                                                                                  |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 130 D                                                                                    |



## DIMENSIONES US STANDARD

|            |          |         |                 |
|------------|----------|---------|-----------------|
| CÓDIGO USA | 94063147 | RC (IN) | 144.9           |
| SW (IN)    | 16.5     | RIM REC | W 13            |
| OD (IN)    | 49.1     | RIM ALT | W 12 ; W 14 L   |
| SLR (IN)   | 21.8     | ECE     | E11-106R-005826 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   |
|-----------|------|------|------|------|------|------|
| 40        | 2300 | 2690 | 3060 | 3440 | 3810 | 4190 |
| 30        | 2420 | 2820 | 3220 | 3620 | 4010 | 4400 |
| 25        | 2540 | 2940 | 3360 | 3770 | 4190 | 4600 |
| 20        | 2660 | 3090 | 3530 | 3960 | 4390 | 4820 |
| 5 LT      | 3100 | 3600 | 4110 | 4620 | 5130 | 5620 |
| 5 HT      | 2660 | 3090 | 3530 | 3960 | 4390 | 4820 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.