


AGRIMAX V-FLECTO



TYRE SIZE	VF 710/70 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STEEL BELTED SPL
TYRE TYPE	TL

DIMENSIONS US STANDARD

USA CODE	94075829	RC (IN)	245.4
SW (IN)	28.3	RIM REC	DW 25 B
OD (IN)	81.0	RIM ALT	DW 23 B; DW 24 B
SLR (IN)	36.5	ECE	E11-106R-009053

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	52
45	8540	9920	11310	12930	14310	15700	17310	18230	20070	21690	23070
FROM 40 TO 25	9380	10900	12420	14200	15720	17240	19010	20030	22060	23830	25350
20	9580	11120	12680	14480	16040	17590	19400	20440	22510	24320	25860
12	9770	11340	12930	14770	16360	17930	19770	20830	22950	24790	26370
5	10330	11990	13670	15620	17290	18970	20920	22030	24270	26220	27890
UPTO 20 CYC	10650	12380	14100	16110	17850	19560	21580	22730	25030	27050	28770
UPTO 10 CYC	12710	14770	16830	19230	21300	23360	25760	27140	29880	32300	34350
UPTO 5CYC	13930	16190	18450	21090	23350	25610	28240	29740	32760	35390	37640
5 HT	9580	11120	12680	14480	16040	17590	19400	20440	22510	24320	25860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.