

# AGRIMAXFACTOR

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 710/70 R 38                                                                              |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRACTOR                                                                                  |
| VERSION      | STANDARD                                                                                 |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 166 D ; 169 A8                                                                           |



## ABMESSUNGEN IS STANDARD

|          |      |          |                 |
|----------|------|----------|-----------------|
| SW (MM)  | 716  | RIM REC  | DW 23 B         |
| OD (MM)  | 1959 | ECE      | E11-106R-007636 |
| SLR (MM) | 866  | SRI      | 925             |
| RC (MM)  | 5800 | TRA CODE | R1W             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 65         | 2915 | 3395 | 3870 | 4350 | 4825 | 5300 |
| 50         | 3065 | 3565 | 4065 | 4565 | 5065 | 5565 |
| 40         | 3195 | 3720 | 4240 | 4765 | 5285 | 5805 |
| 30         | 3355 | 3905 | 4450 | 5000 | 5550 | 6095 |
| 10 LT      | 3910 | 4550 | 5190 | 5830 | 6470 | 7105 |
| 10 HT      | 3355 | 3905 | 4450 | 5000 | 5550 | 6095 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.