


# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>280/70 R 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / МАШИНА ДЛЯ СБОРА ФРУКТОВ / МИНИ- ТРАКТОР / ТРАКТОР-ТЯГАЧ / КОМБАЙН
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	114 A8 ; 114 B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94065707	<b>RC (IN)</b>	100.4
<b>SW (IN)</b>	11.4	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	33.1	<b>RIM ALT</b>	W 8 ; W 10
<b>SLR (IN)</b>	15.4	<b>ECE</b>	E11-106R-006473

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1230	1420	1630	1830	2040	2240	2450	2610
25	1230	1420	1630	1830	2040	2240	2450	2610
20	1320	1520	1740	1970	2190	2410	2630	2790
5 LT	1650	1900	2180	2450	2740	3010	3290	3500
5 HT	1320	1520	1740	1970	2190	2410	2630	2790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.