

AGRIMAX RT 855

TIRE SIZE	280/85 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	118 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94047499	RC (IN)	140.1
SW (IN)	11.5	RIM REC	W 10
OD (IN)	46.7	RIM ALT	W 9
SLR (IN)	21.5	ECE	E4-106R-000614

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	1610	1860	2130	2390	2660	2910
25	1610	1860	2130	2390	2660	2910
20	1720	2010	2280	2570	2840	3120
5 LT	2150	2500	2850	3210	2560	3900
5 HT	1720	2010	2280	2570	2840	3120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.