

AGRIMAX RT 955

| | |
|---------------------|--------------------------------------------------------------------------------------------------------|
| TIRE SIZE | 300/95 R 46 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 148 D ; 151 A8 |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|--------------------------|
| USA CODE | 94076154 | RC (IN) | 209.4 |
| SW (IN) | 11.6 | RIM REC | W 9 |
| OD (IN) | 68.4 | RIM ALT | W 10; W 11; DW 10; DW 11 |
| SLR (IN) | 32.0 | ECE | E11-106R-0010269 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 40 | 8110 | 8980 | 9850 | 10280 | 10860 | 11150 | 11440 | 12020 | 12600 | 13030 |
| 30 | 8770 | 9720 | 10640 | 11120 | 11740 | 12060 | 12370 | 12990 | 13630 | 14090 |
| 25 | 8940 | 9910 | 10860 | 11350 | 11990 | 12310 | 12630 | 13250 | 13900 | 14390 |
| 20 | 9120 | 10100 | 11070 | 11570 | 12220 | 12550 | 12870 | 13520 | 14170 | 14660 |
| 5 | 9650 | 10690 | 11710 | 12230 | 12920 | 13270 | 13610 | 14290 | 14980 | 15500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.