

AS 504

TIRE SIZE	7.5L - 15
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	HD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	100 A8
LI/SS FREE ROLLING	113 A8



РАЗМЕРЫ US STANDARD

USA CODE	94040711	RC (IN)	89.8
SW (IN)	8.3	RIM REC	6 LB
OD (IN)	30.1	RIM ALT	5 K; 5½ J; 5½ K
SLR (IN)	13.9	ECE	E11-106R-004240

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	54
5 FR	3550
15 FR	3020
20 FR	2840
25 FR	2540
5 DW	2470
15 DW	2090
20 DW	1970
25 DW	1760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.