


AGRIMAX SPARGO

TIRE SIZE	VF 380/90 R 46 CFO
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	175 D



ABMESSUNGEN IS STANDARD

SW (MM)	390	RIM REC	DW 13 A
OD (MM)	1852	RIM ALT	W 13 A ; DW 12
SLR (MM)	848	ECE	E11-106R-007527-01
RC (MM)	5611	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4	4.6
70	2835	3190	3485	3665	3480	3960	4080	4315	4495	4670	4850	5025	5145	5320	5440	5675	5915	6210
FROM 65 TO 40	3120	3510	3835	4030	4225	4355	4485	4745	4940	5135	5330	5525	5655	5850	5980	6240	6500	6900
30	3180	3580	3910	4110	4305	4440	4570	4835	5035	5235	5435	5635	5765	5965	6095	6360	6630	7040
20	3240	3650	3985	4190	4390	4525	4660	4930	5135	5340	5540	5745	5880	6080	6215	6485	6760	7180
10*	3430	3860	4215	4430	4645	4790	4930	5215	5430	5645	5860	6075	6220	6435	6575	6860	7150	7590
UPTO 15 CYC.	4230	4760	5200	5465	5730	5905	6080	6430	6695	6960	7225	7490	7665	7930	8105	8460	8810	9350
UPTO 30 CYC.	3545	3990	4355	4580	4800	4950	5095	5390	5610	5835	6055	6275	6425	6645	6795	7090	7385	7835

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.