

AW 702

| | |
|---------------------------|--|
| TIRE SIZE | 12.5/80 - 18 |
| UM | US STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS FREE ROLLING | 148 A8 |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94030606 | RC (IN) | 111.3 |
| SW (IN) | 12.1 | RIM REC | W 9 |
| OD (IN) | 38.0 | RIM ALT | 11 |
| SLR (IN) | 17.0 | ECE | E11-106R-004359 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 71 |
|-----------|------|
| 5 FR | 9720 |
| 15 FR | 8270 |
| 20 FR | 7780 |
| 25 FR | 6940 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.