


FL 695

TIRE SIZE	650/55 R 26.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SLÄPVAGN / ARBETSFORDON / SLÄPVAGN
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	178 D



DIMENSIONER IS STANDARD

SW (MM)	630	RIM REC	AG20.00
OD (MM)	1390	RIM ALT	AG22.00
SLR (MM)	630	ECE	E11-106R-007052
RC (MM)	4242	SRI	675

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0	5.5	6.0
65	--	--	--	3375	3900	4425	4875	5325	5850	6225	6600	7050	7500
50	--	--	--	4085	4720	5355	5900	6445	7080	7535	7990	8535	9075
40	--	3370	4185	4590	5305	6020	6630	7245	7960	8470	8980	9590	10200
30	2835	3740	4645	5100	5890	6685	7365	8045	8835	9400	9970	10650	11325
25	2965	3915	4860	5335	6165	6995	7705	8415	9245	9840	10430	11140	11850
20	3095	4085	5075	5570	6435	7305	8045	8790	9655	10275	10890	11635	12375
10	3375	4455	5535	6075	7020	7965	8775	9585	10530	11205	11880	12690	13500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.