

# AS 504

<b>TIRE SIZE</b>	10.0/75 - 15.3
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	TELESKOPLASTARE / ÅKERSLÄP / ARBETSFORDON / TELESKOPLASTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	123 A8
<b>LI/SS FREE ROLLING</b>	135 A8



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94018604	<b>RC (IN)</b>	94.6
<b>SW (IN)</b>	10.4	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	30.9	<b>ECE</b>	E4-106R-001823
<b>SLR (IN)</b>	14.2	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	103
5 FR	6720
15 FR	5720
20 FR	5380
25 FR	4810
5 DW	4780
15 DW	4070
20 DW	3820
25 DW	3420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.