

# DON 2000

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 10.00 - 20  |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> | ❖ BIAS  |
| <b>MACHINERY</b>    | CAMIÃO LIGEIRO / REBOQUE /<br>IMPLEMENTOS AGRÍCOLAS |
| <b>VERSÃO</b>       | INDUSTRIAL TRAILER                                  |
| <b>TIRE TYPE</b>    | TT  |



## DIMENSÕES US STANDARD

|                   |          |                |          |
|-------------------|----------|----------------|----------|
| <b>CÓDIGO USA</b> | 94043866 | <b>RIM ALT</b> | 7.0; 8.0 |
| <b>SW (IN)</b>    | 11.3     | <b>PR</b>      | 18       |
| <b>OD (IN)</b>    | 42.5     |                |          |
| <b>RIM REC</b>    | 7.5      |                |          |

## LOAD CAPACITY (LBS/TIRE)

|                  |   |   |
|------------------|---|---|
| <b>MPH / PSI</b> | - | - |
| -                | - | - |
| -                | - | - |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.