

# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>750/65 R 26 CHO</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	HARVESTER / COTTON PICKER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	166 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94030668	<b>RC (IN)</b>	193.2
<b>SW (IN)</b>	30.1	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	64.4	<b>RIM ALT</b>	DW 23 B
<b>SLR (IN)</b>	28.1	<b>ECE</b>	E4-106R-000810

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35
<b>30</b>	6430	7360	9010	9700	10870	11680
<b>25</b>	6430	7360	9010	9700	10870	11680
<b>20</b>	6890	7890	9630	10390	11640	12510
<b>10 CYC</b>	10600	12150	14850	16000	17930	19280
<b>5 CYC</b>	11570	13260	16200	17460	19560	21030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.