DATA SHEET

PRINTED ON
23-04-2026

RIDEMAX IT 696

TYRE SIZE	**480/80 R 34 IND**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	TRACTOR
VERSION	STANDARD
TYRE TYPE	TL
LI/SS	164 A8 ; 159 D

DIMENSIONS IS STANDARD

SW (MM)	479	**RIM REC**	W 15 L
OD (MM)	1632	**RIM ALT**	W 16 L
SLR (MM)	728	**ECE**	E4-106R-002296
RC (MM)	4894	**SRI**	775

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2
65	2055	2540	2975	3455	3895	4375
50	2210	2725	3195	3715	4185	4700
40	2350	2900	3400	3950	4450	5000
30	2445	3015	3535	4110	4630	5200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..