

# AGRIMAX RT 765

|              |                                                                                                    |
|--------------|----------------------------------------------------------------------------------------------------|
| TIRE SIZE    | 650/75 R 38                                                                                        |
| UM           | US STANDARD                                                                                        |
| CONSTRUCTION |  RADIAL           |
| MACHINERY    | FELDSPRITZE / TRACTOR /<br>TRAUBENERNTEMASCHINE /<br>ERNTEMASCHINE /<br>LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION      | STANDARD                                                                                           |
| TIRE TYPE    | TL                                                                                                 |
| LI/SS        | 169 D                                                                                              |



## ABMESSUNGEN US STANDARD

|          |          |         |                   |
|----------|----------|---------|-------------------|
| USA-CODE | 94063895 | RC (IN) | 229.1             |
| SW (IN)  | 25.8     | RIM REC | DW 21 B           |
| OD (IN)  | 76.4     | RIM ALT | DW 20 B ; DW 23 B |
| SLR (IN) | 34.4     | ECE     | E11-106R-006161   |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15    | 17    | 20    | 23    | 29    | 35    |
|-----------|------|------|-------|-------|-------|-------|-------|-------|
| 40        | 6020 | 6910 | 7940  | 8950  | 9980  | 11000 | 12030 | 12790 |
| 30        | 6320 | 7250 | 8330  | 9400  | 10480 | 11550 | 12620 | 13430 |
| 25        | 6590 | 7570 | 8700  | 9810  | 10930 | 12060 | 13170 | 14010 |
| 15        | 6910 | 7950 | 9130  | 10300 | 11470 | 12650 | 13820 | 14700 |
| 5 LT      | 8060 | 9260 | 10640 | 12000 | 13370 | 14750 | 16110 | 17140 |
| 5 HT      | 6910 | 7950 | 9130  | 10300 | 11470 | 12650 | 13820 | 14700 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.