


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>480/65 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	142 D ; 145 A8



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	W 15 L
<b>OD (MM)</b>	1335	<b>RIM ALT</b>	W 14 L
<b>SLR (MM)</b>	610	<b>ECE</b>	E4-106R-000653
<b>RC (MM)</b>	4091	<b>SRI</b>	650

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	1275	1485	1670	1855	2045	2200	2440	2650
<b>50</b>	1340	1560	1755	1950	2145	2315	2565	2785
<b>40</b>	1395	1625	1830	2030	2235	2410	2670	2900
<b>30</b>	1465	1710	1925	2135	2350	2535	2810	3050
<b>10 LT</b>	1710	1995	2240	2490	2740	2955	3275	3555
<b>10 HT</b>	1465	1710	1925	2135	2350	2535	2810	3050

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.