

# RIB 774 (C)

225/75 - 17.5

**UM** US STANDARD**CONSTRUCTION**  BIAS**MACHINERY** BALYA MAKINESI / BIÇERDÖVER /  
RÖMÖRK / BIÇERDÖVER /  
UYGULAMALI MAKINE**VERSION** STANDARD**TIRE TYPE** TL

134 A8



## UNDEFINED US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94011025 | <b>RC (IN)</b> | 90.9            |
| <b>SW (IN)</b>  | 8.7      | <b>RIM REC</b> | 6.75            |
| <b>OD (IN)</b>  | 30.5     | <b>ECE</b>     | E11-106R-004657 |
| <b>SLR (IN)</b> | 14.2     | <b>PR</b>      | 12              |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>100</b> |
|------------------|------------|
| 5 FR             | 6550       |
| 15 FR            | 5570       |
| 20 FR            | 5240       |
| 25 FR            | 4670       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.