

# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>215/65 R 14</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VINDIMADORA / MAQUINA PARA RECOLHA DOS FRUTOS / TRATOR PEQUENO / TRATOR / CEIFEIRA
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	90 A8 ; 90 B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94076277	<b>RC (IN)</b>	75.0
<b>SW (IN)</b>	8.7	<b>RIM REC</b>	W 7
<b>OD (IN)</b>	24.8	<b>RIM ALT</b>	W 6
<b>SLR (IN)</b>	11.4	<b>ECE</b>	E11-106R-0010331

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
30	620	720	830	920	1030	1130	1330
25	620	720	830	920	1030	1130	1330
20	670	780	890	1000	1110	1220	1430
5 LT	830	960	1110	1240	1370	1520	1780
5 HT	670	780	890	1000	1110	1220	1430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.