

# AGRIMAX RT 855

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>280/85 R 20</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | PULVERIZADOR AGRÍCOLA /<br>VINDIMADORA / TRATOR / CEIFEIRA /<br>IMPLEMENTOS AGRÍCOLAS    |
| <b>VERSÃO</b>       | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 122 A8/B   |



## DIMENSÕES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94072927 | <b>RC (IN)</b> | 117.2           |
| <b>SW (IN)</b>    | 11.5     | <b>RIM REC</b> | W 10            |
| <b>OD (IN)</b>    | 38.7     | <b>RIM ALT</b> | W 9             |
| <b>SLR (IN)</b>   | 17.6     | <b>ECE</b>     | E11-106R-007936 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35   |
|-----------|------|------|------|------|------|------|------|------|
| 30        | 1360 | 1590 | 1820 | 2050 | 2280 | 2480 | 2940 | 3310 |
| 25        | 1360 | 1590 | 1820 | 2050 | 2280 | 2480 | 2940 | 3310 |
| 20        | 1450 | 1710 | 1950 | 2200 | 2450 | 2660 | 3150 | 3540 |
| 5 LT      | 1820 | 2130 | 2450 | 2760 | 3060 | 3330 | 3950 | 4430 |
| 5 HT      | 1450 | 1710 | 1950 | 2200 | 2450 | 2660 | 3150 | 3540 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.