


EARTHMAX SR 49 M

| | |
|---------------------|--|
| TIRE SIZE | 26.5 R 25 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BULLDOZER / GRUVLASTMASKIN / HJULLASTARE / DUMPER MED LÅGPROFIL |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 193 B ; 202 A2 |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|-----------|--------------------|-------|
| OD (MM) | 1782 | TRA CODE | E4/L4 |
| SLR (MM) | 801 | STAR RATING | ★★/★ |
| RC (MM) | 5297 | | |
| RIM REC | 22.00/3.0 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 | 5.25 |
|------------|-------|-------|-------|-------|-------|-------|
| 50 | 9500 | 9750 | 10300 | 10600 | 11200 | 11500 |
| 10 | 12850 | 13200 | 14000 | 14500 | 15000 | - |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.