


AGRIMAX V- FLECTO

TIRE SIZE	VF 540/65 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	162 D



DIMENSIONS US STANDARD

CODE USA	94059119	RC (IN)	196.1
SW (IN)	21.6	RIM REC	DW 20 B
OD (IN)	66.0	RIM ALT	DW 18 L
SLR (IN)	29.9	ECE	E11-106R-005020

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	4850	5610	6370	7240	7900	8580	9520
FROM 40 TO 25	5330	6170	7010	7960	8690	9420	10470
20	5430	6290	7140	8110	8850	9610	10680
12	5540	6420	7290	8270	9030	9800	10890
5	5860	6790	7700	8750	9550	10360	11520
*UPTO 5 CYC WITH FRONT LOADER	7460	8640	9810	11130	12160	13190	14660
5 HT	5430	6290	7140	8110	8850	9610	10680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.