


# EARTHMAX SR 53

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 17.5 R 25                                                                                |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | БУЛЬДОЗЕР / ПОГРУЗЧИК /<br>НИЗКОПРОФИЛЬНЫЙ САМОСВАЛ                                      |
| VERSION      | CUT RESISTANT COMPOUND                                                                   |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 188 A2                                                                                   |



## РАЗМЕРЫ IS STANDARD

|          |           |             |     |
|----------|-----------|-------------|-----|
| OD (MM)  | 1400      | TRA CODE    | L5  |
| SLR (MM) | 637       | STAR RATING | ★★★ |
| RC (MM)  | 4214      |             |     |
| RIM REC  | 14.00/1.5 |             |     |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 6.75 | 7.00 | 7.25 | 7.50 | 7.75 | 8.00  |
|------------|------|------|------|------|------|-------|
| 10         | 8750 | 9000 | 9250 | 9500 | 9750 | 10000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.