

AGRIMAX V-FLECTO

TIRE SIZE	VF 900/60 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATTORE A ELEVATA POTENZA / TRATTORE
VERSIONE	STEEL BELTED
TIRE TYPE	TL
LI/SS	195 D



DIMENSIONI IS STANDARD

SW (MM)	900	RIM REC	DW 30B
OD (MM)	2142	ECE	E11-106R-0010587
SLR (MM)	944	SRI	1025
RC (MM)	6410		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8
70	4645	5420	6085	6855	7630	8405	9400	10065	11055
FROM 65 TO 40	5105	5955	6685	7535	8385	9235	10330	11060	12150
30	5205	6075	6815	7685	8550	9420	10535	11275	12390
20	5310	6195	6950	7835	8720	9605	10740	11500	12635
10	5615	6550	7355	8290	9225	10160	11365	12165	13365
UPTO 30 CYCLIC	5795	6760	7585	8550	9520	10485	11725	12550	13790
UPTO 15 CYCLIC	6915	8070	9055	10210	11360	12510	13995	14980	16460
UPTO 10 CYCLIC	7580	8845	9925	11190	12455	13715	15340	16425	18045
10HT	5205	6075	6815	7685	8550	9420	10535	11275	12390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.