

# TR 678

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 710/55 - 34  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> | ❖ BIAS   |
| <b>MACHINERY</b>    | OUTILLAGE AGRICOLE / REMORQUE /<br>OUTILLAGE AGRICOLE / PORTEUR /<br>PELLETEUSE / REMORQUE |
| <b>VERSION</b>      | STEEL BELTED   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 168 A2 ; 163 A6  |



## DIMENSIONS IS STANDARD

|                 |      |                 |                 |
|-----------------|------|-----------------|-----------------|
| <b>SW (MM)</b>  | 700  | <b>RIM REC</b>  | DW 24 B         |
| <b>OD (MM)</b>  | 1640 | <b>ECE</b>      | E11-106R-007156 |
| <b>SLR (MM)</b> | 757  | <b>PR</b>       | 14              |
| <b>RC (MM)</b>  | 4890 | <b>TRA CODE</b> | LS2             |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.40</b> |
| 30                | 4875        |
| 10                | 5600        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.