



ROCK GRIP E4



Description

ROCK GRIP (E-4) is a bias-ply tyre specially designed for haul trucks in mining service and quarry operations. Whenever your short-haul site conditions require both heat resistance and cut protection, ROCK GRIP is the tyre you can rely upon.

UM

IS Standard

Construction

⌘ Bias

Machinery

OTR ■ Rigid Dump Truck

Version	STANDARD
Tyre Type	TT
Tyre size	18.00-33
LI/SS	

Dimensions IS Standard

OD (mm)	1887
SLR (mm)	869
RC (mm)	5586
Rim Rec	13.00/2.5
TRA Code	E4

Load Capacity (IS)

km/h / bar	6.50	8.50
50	11200	-
10	-	18500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..