

# SM 55 L5S

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 17.5 - 25  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  |
| <b>MACHINERY</b>    | UNDERGROUND MINING VEHICLE /<br>LOW PROFILE DUMP TRUCK |
| <b>VERSION</b>      | ARASHIELD  |
| <b>TIRE TYPE</b>    | TL   |



## DIMENSIONS IS STANDARD

|                 |           |                 |                           |
|-----------------|-----------|-----------------|---------------------------|
| <b>OD (MM)</b>  | 1375      | <b>RIM ALT</b>  | 14.00/1.3; 14.00/1.4 (DC) |
| <b>SLR (MM)</b> | 631       | <b>PR</b>       | 24                        |
| <b>RC (MM)</b>  | 4043      | <b>TRA CODE</b> | L5S                       |
| <b>RIM REC</b>  | 14.00/1.5 |                 |                           |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>6.75</b> |
|-------------------|-------------|
| 10                | 9060        |
| 15                | 7880        |
| 25                | 7250        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.