

# AGRIMAX RT 955

<b>TIRE SIZE</b>	<b>270/80 R 36</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	134 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94067046	<b>RC (IN)</b>	161.0
<b>SW (IN)</b>	10.8	<b>RIM REC</b>	W9
<b>OD (IN)</b>	53.0	<b>RIM ALT</b>	W8; W10
<b>SLR (IN)</b>	24.8	<b>ECE</b>	E11-106R-006758

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	52	58
30	1640	1920	2200	2480	2770	3000	3330	3510	3840	4170	4440	4670
25	1640	1920	2200	2480	2770	3000	3330	3510	3840	4170	4440	4670
20	1750	2060	2360	2660	2950	3210	3560	3760	4110	4460	4760	5000
5	2460	2880	3300	3730	4140	4500	4980	5260	5750	6250	6670	7010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.