

# TR 135

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>18.4 - 30</b>   |
| <b>UM</b>        | IS STANDARD        |
| <b>MACHINERY</b> | TRACTOR / REMOLQUE |
| <b>VERSIÓN</b>   | STANDARD           |
| <b>TIRE TYPE</b> | TT                 |
| <b>LI/SS</b>     | 151 A6             |



## DIMENSIONES IS STANDARD

|                 |        |                         |                 |
|-----------------|--------|-------------------------|-----------------|
| <b>OD (MM)</b>  | 1545   | <b>ECE</b>              | E11-106R-003612 |
| <b>SLR (MM)</b> | 697    | <b>PR</b>               | 14              |
| <b>RC (MM)</b>  | 4712   | <b>SRI</b>              | 725             |
| <b>RIM REC</b>  | W 16 L | <b>TRA CODE</b>         | R1              |
| <b>RIM ALT</b>  | W 15 L | <b>TREAD DEPTH (MM)</b> | 38              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.60</b> |
| 30                | 3450        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.