


AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 520/85 R 46 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 158 A8/B |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------------------------|
| USA-CODE | 94030569 | RC (IN) | 242.4 |
| SW (IN) | 20.3 | RIM REC | DW 16 L ; W 16 A ; W 16 L ; DD 16 |
| OD (IN) | 80.8 | RIM ALT | DW 18 L ; W 18 L ; W 18 A |
| SLR (IN) | 36.6 | ECE | E4-106R-001415 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|-------|-------|-------|
| 30 | 5160 | 6000 | 6840 | 7680 | 8530 | 9370 |
| 25 | 5160 | 6000 | 6840 | 7680 | 8530 | 9370 |
| 20 | 5520 | 6430 | 7330 | 8230 | 9140 | 10030 |
| 5 LT | 6910 | 8040 | 9170 | 10300 | 11430 | 12550 |
| 5 HT | 5520 | 6430 | 7330 | 8230 | 9140 | 10030 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.