


# EARTHMAX SR 25 PLUS



<b>TIRE SIZE</b>	<b>14.00 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PLANIERER / RADLADER / PLANIERER / RADLADER / PLANIERER / PLANIERER
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	153 A8 ; 175 A2

## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94044962	<b>RIM REC</b>	8.00TG
<b>OD (IN)</b>	54.0	<b>RIM ALT</b>	9.00GR
<b>SLR (IN)</b>	24.6	<b>TRA CODE</b>	G2/L2
<b>RC (IN)</b>	163.2	<b>STAR RATING</b>	★

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	29	33	36	40	44	47	51	54	76	80
25	4940	5360	5840	6150	6600	7150	7400	8050	-	-
5	-	-	-	-	-	-	-	-	14800	15200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.