

FLOTATION 648

TIRE SIZE	700/50 - 22.5
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	PRESSA PER BALLE DI FIENO / MIETITREBBIA / SPARGITORE / MIETITREBBIA / ATTREZZI AGRICOLI
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	162 A8/158 B
LI/SS FREE ROLLING	174 A8/170 B



DIMENSIONI IS STANDARD

SW (MM)	700	RIM REC	24.00
OD (MM)	1270	ECE	E4-106R-001566
SLR (MM)	550	PR	16
RC (MM)	3775		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.00	2.20	2.40
10 FR	8430	8910	9380
20 FR	7585	8020	8440
30 FR	6740	7130	7505
40 FR	6020	6365	6700
50 FR	5420	5730	6000
10 DW	5980	6320	6650
20 DW	5380	5690	5985
30 DW	4780	5055	5320
40 DW	4270	4515	4750
50 DW	3845	4065	4250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.