

# AW 909

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>10.0/80 - 12</b>  |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       | ⊠ BIAS   |
| <b>MACHINERY</b>          | ENFARDADEIRA DE FENO /<br>IMPLEMENTOS AGRÍCOLAS /<br>REBOQUE / CEIFEIRA / IMPLEMENTOS<br>AGRÍCOLAS |
| <b>VERSÃO</b>             | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 121 A8   |



## DIMENSÕES IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 264  | <b>RIM REC</b> | 9.00           |
| <b>OD (MM)</b>  | 710  | <b>RIM ALT</b> | 7.0            |
| <b>SLR (MM)</b> | 313  | <b>ECE</b>     | E4-106R-002662 |
| <b>RC (MM)</b>  | 2080 | <b>PR</b>      | 10             |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>3.90</b> |
|-------------------|-------------|
| <b>10 FR</b>      | 2030        |
| <b>25 FR</b>      | 1725        |
| <b>30 FR</b>      | 1625        |
| <b>40 FR</b>      | 1450        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.