


AGRIMAX RT 855

| | |
|---------------------|--|
| TYRE SIZE | 320/85 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 124 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 329 | RIM REC | W 11 |
| OD (MM) | 1255 | RIM ALT | W 9 ; W 10 |
| SLR (MM) | 569 | ECE | E4-106R-000615 |
| RC (MM) | 3743 | SRI | 600 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 50 | 880 | 1025 | 1170 | 1315 | 1460 | 1600 |
| 40 | 880 | 1025 | 1170 | 1315 | 1460 | 1600 |
| 30 | 945 | 1100 | 1255 | 1410 | 1565 | 1715 |
| 10 LT | 1180 | 1375 | 1570 | 1760 | 1955 | 2145 |
| 10 HT | 945 | 1100 | 1255 | 1410 | 1565 | 1715 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.